

Logic

Dr. Melanie Martin
CS 4480
October 12, 2012
Based on slides from
<http://aima.eecs.berkeley.edu/2nd-ed/slides-ppt/>

Entailment


- Entailment means that one thing follows from another:

$$KB \vdash \alpha$$

- Knowledge base KB entails sentence α if and only if α is true in all worlds where KB is true
 - E.g., the KB containing "the Giants won" and "the Reds won" entails "Either the Giants won or the Reds won"
 - E.g., $x+y = 4$ entails $4 = x+y$
 - Entailment is a relationship between sentences (i.e., syntax) that is based on semantics


Models

- Logicians typically think in terms of models, which are formally structured worlds with respect to which truth can be evaluated
- We say m is a model of a sentence α if α is true in m
- $M(\alpha)$ is the set of all models of α
- Then $KB \models \alpha$ iff $M(KB) \subseteq M(\alpha)$
 - E.g. $KB = \text{Giants won and Reds won}$
 $\alpha = \text{Giants won}$



Entailment in the wumpus world


Situation after detecting nothing in [1,1], moving right, breeze in [2,1]




Consider possible models for KB assuming only pits

3 Boolean choices \Rightarrow 8 possible models

Wumpus models




Wumpus models




- $KB = \text{wumpus-world rules} + \text{observations}$

Wumpus models




- KB = wumpus-world rules + observations
- α_1 = "[1,2] is safe", $KB \models \alpha_1$, proved by **model checking**

Wumpus models



- KB = wumpus-world rules + observations

Wumpus models



- KB = wumpus-world rules + observations
- α_2 = "[2,2] is safe", $KB \models \alpha_2$

Inference

- $KB \vdash \alpha$ = sentence α can be derived from KB by procedure i
- **Soundness**: i is sound if whenever $KB \vdash \alpha$, it is also true that $KB \models \alpha$
- **Completeness**: i is complete if whenever $KB \models \alpha$, it is also true that $KB \vdash \alpha$
- Preview: we will define a logic (first-order logic) which is expressive enough to say almost anything of interest, and for which there exists a sound and complete inference procedure.
- That is, the procedure will answer any question whose answer follows from what is known by the KB .

Propositional logic: Syntax

- Propositional logic is the simplest logic – illustrates basic ideas
- The proposition symbols P_1, P_2 etc are sentences
 - If S is a sentence, $\neg S$ is a sentence (**negation**)
 - If S_1 and S_2 are sentences, $S_1 \wedge S_2$ is a sentence (**conjunction**)
 - If S_1 and S_2 are sentences, $S_1 \vee S_2$ is a sentence (**disjunction**)
 - If S_1 and S_2 are sentences, $S_1 \Rightarrow S_2$ is a sentence (**implication**)
 - If S_1 and S_2 are sentences, $S_1 \Leftrightarrow S_2$ is a sentence (**biconditional**)

Propositional logic: Semantics

Each model specifies true/false for each proposition symbol

E.g. $P_{1,2}$ $P_{2,2}$ $P_{3,1}$
false true false

With these symbols, 8 possible models, can be enumerated automatically.

Rules for evaluating truth with respect to a model m :

$\neg S$ is true iff S is false
 $S_1 \wedge S_2$ is true iff S_1 is true and S_2 is true
 $S_1 \vee S_2$ is true iff S_1 is true or S_2 is true
 $S_1 \Rightarrow S_2$ is true iff S_1 is false or S_2 is true
 i.e., $S_1 \Rightarrow S_2$ is false iff S_1 is true and S_2 is false
 $S_1 \Leftrightarrow S_2$ is true iff $S_1 \Rightarrow S_2$ is true and $S_2 \Rightarrow S_1$ is true

Simple recursive process evaluates an arbitrary sentence, e.g.,

$\neg P_{1,2} \wedge (P_{2,2} \vee P_{3,1}) = \text{true} \wedge (\text{true} \vee \text{false}) = \text{true} \wedge \text{true} = \text{true}$

Truth tables for connectives

P	Q	$\neg P$	$P \wedge Q$	$P \vee Q$	$P \Rightarrow Q$	$P \Leftrightarrow Q$
false	false	true	false	false	true	true
false	true	true	false	true	true	false
true	false	false	false	true	false	false
true	true	false	true	true	true	true